

STU-HL40053MG

404nm /500mW Violet Laser Diode

Features

- Optical output power: 400mW (CW)
- Violet Lasing: 398~410nm
- Low operating current: 370mA Typ.
- Low operating voltage: 4.9V Max.
- Package: 5.6mm
- Multiple transverse mode
- TE mode oscillation



Applications

- Bio & Medical
- Measurement

Absolute Maximum Ratings($T_c=25^\circ\text{C}$)







Item	Symbol	Ratings	Unit
Optical output power	P_o	500	mW
LD Reverse Voltage	$V_{R(LD)}$	5	V
Operating Temperature	T_{opr}	0 ~ +30	$^\circ\text{C}$
Storage Temperature	T_{stg}	-35 ~ +85	$^\circ\text{C}$



* Monitor PD for initial checking purpose only

Optical and Electrical Characteristics($T_c=25^\circ\text{C}$)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Threshold current	I_{th}	-	110	130	mA	-
Operating current	I_{op}	-	370	410	mA	$P_o=400\text{mW}$
Operating voltage	V_{op}	-	-	4.9	V	$P_o=400\text{mW}$
Beam divergence Parallel to the junction	$\theta_{//}$	5	13	25	$^\circ$	$P_o=400\text{mW},$ Full angle $1/e^2$
Beam divergence Perpendicular to the junction	θ_{\perp}	30	42	50	$^\circ$	$P_o=400\text{mW},$ Full angle $1/e^2$
Lasing Wavelength	λ_p	398	404	410	nm	$P_o=400\text{mW}$

* Monitor PD for initial checking purpose only

Typical Characteristic Curves


Outline & Internal Circuit


(2) (flange)